


G3725502

G3726002

G3726029

CÓDIGO	G3725502	G3726002	G3726029
Salida	24 VDC		
Carga Máxima	630 mA	2000 mA	2500 mA
Montaje	Riel DIN		
Tamaño / Peso	25 x 93 x 56 mm / 100 g	78 x 93 x 56 mm / 300 g	103,7 x 32 x 97,5 mm / 270 g
Alimentación	85 - 264 VAC / 120 - 370 VDC		90 - 264 VAC / 127 - 370 VDC
Temperatura ambiente para instrumento	-20 + 60 °C		-25 + 50 °C


D1020172

D1020180

D1020199

CÓDIGO	D1020172	D1020180	D1020199
Salida	24 VDC		
Carga Máxima	5000 mA	10000 mA	20000 mA
Montaje	Riel DIN		
Tamaño / Peso	66 x 125 x 100 mm 790 g	126 x 126 x 100 1200 g	227 x 125 x 100 mm 2400 g
Alimentación	88 - 132 VAC / 176 - 264 VAC Seleccionables 248 - 370 VDC	85 - 264 VAC 120 - 370 VDC	180 - 264 VAC 250 - 370 VDC
Temperatura ambiente para instrumento	-10 + 60 °C	-10 + 70 °C	